

SMPS

ilcoPower PS3

Fields of application

Worldwide usable power supply with low stand-by consumption and 3A rating.

ilcon
LINEAR ACTUATOR CONCEPTS

Advantages

- Switching power supply with wide range input
- Output load up to 7 A max. for 2 min
- Input voltage 100-240 V, 50 Hz/60 Hz
- Output voltage 29 V
- Color: RAL9005 black



Product details

| Parameter | Comments | Min | Typical | Max | Unit |
|---------------------------|---|-----|-------------|-----|------|
| Supply voltage | | 100 | | 240 | V |
| Supply frequency | | 45 | | 65 | Hz |
| Standby power consumption | | | Level VI | | |
| Type of protection | | | II | | |
| Color: | RAL9005 Black | | black | | |
| Duty cycle | Max 2 minutes continuous operation followed by 18 min. stop | | 10 | | % |
| Storage temperature | non-condensing | 0 | | +40 | ° C |
| Ambient temperature | non-condensing | +10 | | +40 | ° C |
| Approvals | | | CE, UL, CUL | | |

Order key 409112

ilcon GmbH
Linear Actuator Concepts
Hertzstr. 1-3
27318 Hoya
Germany
Phone +49 4251 816610-10
www.ilcon.com
info@ilcon.com

ilcon Actuator Corp.
Linear Actuator Concepts
11511 James Street
Holland, MI 49424
USA

Phone (616) 796-3235
www.ilcon.com
info@ilcon.com

For more detailed data sheets, please contact our Sales Department. We would be pleased to provide a documentation according to your product specifications. Mistakes and printing errors excepted. If you have any questions, please do not hesitate to contact us.
Dated: 11/10/2017